

U.S. DEPARTMENT OF COMMERCE/ National Oceanic and Atmospheric Administration

OFCM



OFFICE OF THE FEDERAL COORDINATOR FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH

FEDERAL METEOROLOGICAL HANDBOOK NO. 11

DOPPLER RADAR METEOROLOGICAL OBSERVATIONS

PART B
DOPPLER RADAR THEORY
AND METEOROLOGY

FCM-H11B-2005

Washington, DC
December 2005



THE FEDERAL COMMITTEE FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH (FCMSSR)

VADM CONRAD C. LAUTENBACHER, JR., USN (RET.)
Chairman, Department of Commerce

DR. SHARON HAYS (Acting)
Office of Science and Technology Policy

DR. RAYMOND MOTHAK
Department of Agriculture

BRIG GEN DAVID L. JOHNSON, USAF (RET.)
Department of Commerce

MR. ALAN SHAFFER
Department of Defense

DR. ARISTIDES PATRINOS
Department of Energy

DR. MAUREEN MCCARTHY
Science and Technology Directorate
Department of Homeland Security

DR. MICHAEL SOUKUP
Department of the Interior

MR. RALPH BRAIBANTI
Department of State

MR. RANDOLPH LYON
Office of Management and Budget

MR. CHARLES E. KEEGAN
Department of Transportation

MR. DAVID MAURSTAD (Acting)
Federal Emergency Management Agency
Department of Homeland Security

DR. MARY L. CLEAVE
National Aeronautics and Space
Administration

DR. MARGARET S. LEINEN
National Science Foundation

MR. PAUL MISENCIK
National Transportation Safety Board

MR. JAMES WIGGINS
U.S. Nuclear Regulatory Commission

DR. LAWRENCE REITER
Environmental Protection Agency

MR. SAMUEL P. WILLIAMSON
Federal Coordinator

MR. JAMES B. HARRISON, Executive Secretary
Office of the Federal Coordinator for
Meteorological Services and Supporting Research

THE INTERDEPARTMENTAL COMMITTEE FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH (ICMSSR)

MR. SAMUEL P. WILLIAMSON, Chairman
Federal Coordinator

MR. THOMAS PUTERBAUGH
Department of Agriculture

MR. JOHN E. JONES, JR.
Department of Commerce

MR. ROBERT WINOKUR, USN (Acting)
United States Navy
Department of Defense

BRIG GEN THOMAS E. STICKFORD, USAF
United States Air Force
Department of Defense

MR. RICKEY PETTY
Department of Energy

MR. CHRISTOPHER DOYLE
Science and Technology Directorate
Department of Homeland Security

MR. JOHN VIMONT
Department of the Interior

MS. REGINA MCELROY
Federal Highway Administration
Department of Transportation

MS. LISA BEE
Federal Aviation Administration
Department of Transportation

DR. JONATHAN M. BERKSON
United States Coast Guard
Department of Homeland Security

MR. JEFFREY MACLURE
Department of State

DR. S. T. RAO
Environmental Protection Agency

MR. JOHN GAMBEL
Federal Emergency Management Agency
Department of Homeland Security

DR. RAMESH KAKAR
National Aeronautics and Space
Administration

DR. JARVIS MOYERS
National Science Foundation

MR. DONALD E. EICK
National Transportation Safety Board

MS. LETA A. BROWN
U.S. Nuclear Regulatory Commission

MS. ANDREA PETRO
Office of Management and Budget

MR. JAMES B. HARRISON, Executive Secretary
Office of the Federal Coordinator for
Meteorological Services and Supporting Research

FEDERAL COORDINATOR FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH

DOPPLER RADAR
METEOROLOGICAL OBSERVATIONS

FEDERAL
METEOROLOGICAL
HANDBOOK NO. 11
DECEMBER 2005

PART B
DOPPLER RADAR THEORY
AND METEOROLOGY

FCM-H11B-2005

Washington, DC

PREFACE

The Federal Coordinator for Meteorological Services and Supporting Research has the responsibility to maintain and publish Federal Meteorological Handbooks. This series of documents provides standards and procedures to facilitate the efficient collection, sharing, and use of meteorological information by agencies of the federal government and private industry.

The original Federal Meteorological Handbook, Number 11 (FMH-11), DOPPLER RADAR METEOROLOGICAL OBSERVATIONS, was prepared and published under the auspices of the Office of the Federal Coordinator for Meteorological Services and Supporting Research (OFCM) at the request of the Next Generation Weather Radar (NEXRAD) Program Council and in coordination with the federal agencies that are represented on the Interdepartmental Committee for Meteorological Services and Supporting Research. The purpose of FMH-11 is to standardize, insofar as practical, the operation of the Weather Surveillance Radar-1988, Doppler (WSR-88D) systems and the procedures used by personnel of the Departments of Commerce, Defense, and Transportation. By approving publication of this handbook, those agencies have agreed to operate their WSR-88D systems accordingly. Some flexibility under certain meteorological, siting, or mission circumstances is permitted to enhance the quality and utility of some WSR-88D products.

The revision process is dependent on the evolution of WSR-88D subsystems software and products. Part A has been revised to ensure it provides users current operations guidance. Parts B, C, and D are being revised in a separate effort principally through the guidance of the Radar Operations Center (ROC). All revisions are coordinated among the NEXRAD triagencies (Department of Commerce (DoC), Department of Defense (DoD), and Department of Transportation (DoT)); thus, they possess the same authority as the initial edition of FMH-11.

The agencies shall review the documents at least annually. The goal is to review and update (as necessary) the handbooks as part of every WSR-88D software build release. Suggestions for modifications and additions shall be forwarded through the appropriate channels in each agency for consideration, and issuance, if appropriate. Changes will be issued as a total update of each chapter of the handbook. The handbook updates will be issued in electronic format and made available on the OFCM home page (<http://www.ofcm.gov>). Readers can make copies of the handbook without a request for approval from the OFCM. A summary of changes made during updates will be annotated in the preface of each part.

Each major part of the FMH-11 is designed to stand alone, except where cross references avoid voluminous redundancy. In all, FMH-11 has four parts:

- Part A - System Concepts, Responsibilities, and Procedures (December 2005)
- Part B - Doppler Radar Theory and Meteorology (December 2005)
- Part C - WSR-88D Products and Algorithms (February 1991)
- Part D - WSR-88D Unit Description and Operational Applications (April 1992)

Part B brings together in one document most of the theory required to understand how the WSR-88D acquires and processes the Doppler radar signal. It presents mathematical formulations of the physical processes and laws, explains how the Doppler technology “sees” various meteorological and hydrological events, and explores the strengths and problems in data acquisition with a Doppler radar. It then addresses aspects of radar meteorology regarding recognition of velocity patterns and applications of Doppler radar to storm events.

Summary of Changes:

This version of Part B updates and replaces the original document, published in June, 1990. This version updates the document as of Radar Product Generator Build 6 (released in September 2004) and provides updated information related to large-scale precipitation weather systems and individual thunderstorms and attendant phenomena. The section related to hurricanes has been deleted, but may be updated and included in a future version.

Samuel P. Williamson
Federal Coordinator for Meteorological
Services and Supporting Research

**FEDERAL METEOROLOGICAL HANDBOOK NO. 11
DOPPLER RADAR METEOROLOGICAL OBSERVATIONS
PART B
DOPPLER RADAR THEORY AND METEOROLOGY**

TABLE OF CONTENTS

	Page
PREFACE	ii
TABLE OF CONTENTS	iv
LIST OF FIGURES	viii
LIST OF TABLES	xi
LIST OF SYMBOLS	xii
CHAPTER 1. INTRODUCTION	
1.1 Background	1-1
1.2 Purpose and Scope	1-1
1.3 Organization and Content	1-1
1.3.1 Doppler Meteorological Radar Fundamentals	1-1
1.3.2 Radar Meteorology	1-2
1.3.3 Appendices	1-2
CHAPTER 2. INTRODUCTION TO THE WSR-88D	
2.1 General	2-1
2.2 Basic Unit Description	2-1
2.3 WSR-88D Radar Characteristics	2-2
2.4 Fundamental Concepts of Doppler Radar	2-6
2.4.1 Doppler Frequency	2-6
2.4.2 Range-Velocity Ambiguity	2-7
2.4.3 Velocity Measurement	2-9
CHAPTER 3. DATA ACQUISITION CONSIDERATIONS	
3.1 Introduction	3-1
3.2 Temporal and Spatial Sampling	3-1
3.3 Data Recovery by Ground Clutter Suppression	3-9
3.4 Propagation Considerations	3-13
3.4.1 Standard Propagation	3-17
3.4.2 Anomalous Propagation	3-22

	Page
3.5 Signal Attenuation	3-25
3.5.1 Atmospheric Attenuation	3-25
3.5.2 Rainfall Attenuation	3-25
3.5.3 Lack of Beam Filling	3-28
3.6 Data Contamination by Antenna Sidelobe Signal	3-28
CHAPTER 4. WSR-88D FUNCTIONAL OVERVIEW	
4.1 Introduction	4-1
4.2 Simplified Radar System	4-1
4.3 Radar Data Acquisition	4-1
4.3.1 Basic Radar	4-4
4.3.2 Signal Processors	4-4
4.3.3 Post Processing	4-5
4.3.4 Operational Scenario	4-6
4.3.5 Base Data Summary	4-9
4.4 Radar Product Generator	4-12
4.4.1 Interactive Control	4-12
4.4.2 Meteorological Analysis Products	4-12
4.5 User Display Systems	4-13
CHAPTER 5. ESTIMATION OF PRECIPITATION BY RADAR	
5.1 Introduction	5-1
5.2 Physical Principals of the Measurement Process	5-1
5.2.1 Particle Size Distributions	5-1
5.2.2 Radar Reflectivity Factor	5-2
5.2.3 Reflectivity-Precipitation Relationship	5-4
5.3 Error Sources in Radar Measurements	5-4
5.3.1 Estimating Equivalent Radar Reflectivity Factor	5-4
5.3.2 Variations in the Z-R Relationship	5-5
5.3.3 Time and Space Averaging	5-10
5.3.4 Below Beam Effects	5-10
5.3.5 Effects of the Vertical Reflectivity Profile	5-12
5.4 Adjustment of Radar-Derived Precipitation Estimates	5-12
5.4.1 Adjustments Using Radar Parameters Alone	5-12
5.4.2 Adjustment with Rain Gauges	5-13
5.4.3 Adjustments with Other Data	5-14

	Page
5.5 Concluding Remarks	5-14
CHAPTER 6. INTERPRETATION OF DOPPLER VELOCITY PATTERNS	
6.1 Introduction	6-1
6.2 Patterns Due to Vertical Variations of the Wind	6-1
6.3 Quantitative Measurements of Vertical Profiles of the Horizontal Wind	6-6
6.4 Patterns Associated With Convective Storms	6-9
6.5 Concluding Remarks	6-19
CHAPTER 7. MORPHOLOGY OF LARGE-SCALE PRECIPITATING WEATHER SYSTEMS	
7.1 Introduction	7-1
7.1.1 Stratiform Rain and Snow	7-1
7.1.2 Bright Band	7-2
7.2 Mesoscale Convective Systems	7-5
7.3 Squall Lines and Mesoscale Convective Systems	7-7
7.4 Storm Development on Airmass Boundaries	7-19
CHAPTER 8. MORPHOLOGY OF INDIVIDUAL THUNDERSTORMS AND ATTENDANT PHENOMENA	
8.1 Thunderstorm Cells and Their Evolution	8-1
8.2 Types of Thunderstorms	8-7
8.3 Environment Factors Governing Storm Type	8-12
8.4 Storm Motion	8-15
8.5 Radar Reflectivity Structure of Thunderstorms	8-17
8.5.1 Weak Echo Regions	8-17
8.5.2 Ordinary Multicellular or Unicellular Storms in Weak Shear	8-19
8.5.3 Ordinary Multicellular Storms in Moderate to Strong Shear	8-19
8.5.4 Isolated Supercell Storms	8-23
8.5.5 High Precipitation (HP) Supercell Storms	8-27
8.5.6 Low Precipitation (LP) Supercell Storms	8-28
8.5.7 Squall Lines and Mesoscale Convective Systems (MCSs)	8-28
8.5.8 Transformation from One Type of Storm to Another	8-32
8.5.9 Additional Information	8-32
APPENDIX A: PHYSICS OF METEOROLOGICAL RADARS	
A.1 Detection of Precipitation	A-1
A.2 Doppler Effect	A-6
A.3 Statistics of the Raindrop Array	A-9
A.4 Return Power, Velocity, and Spectrum Width Estimation	A-13
APPENDIX B: POINT TARGETS AND CLEAR AIR RETURNS	B-1

	Page
APPENDIX C: ACRONYMS AND ABBREVIATIONS	C-1
APPENDIX D: GLOSSARY	D-1

LIST OF FIGURES

Figure	Page
2-1. Reflectivity Detection Capability of the WSR-88D	2-5
2-2. Example of Sampling a Signal	2-8
2-3. Unambiguous Range-Velocity Relationship for the WSR-88D	2-10
2-4. Velocity Sampling	2-12
2-5. Standard Deviation of the Mean Velocity Estimate	2-15
3-1a. Autocorrelation of Reflectivity with Time	3-2
3-1b. Autocorrelation of Mean Radial Velocity with Time	3-3
3-2. Meteorological Field Spatial Scale Amplitude Weighting Function	3-5
3-3. Sampling and Cutoff Scale Length	3-6
3-4. Cumulative Probability for Convective Storms	3-8
3-5. Histograms of Velocity for Three Tornadoic Storms	3-10
3-6. Standard Deviations of the Velocity Estimates and Ground Clutter Suppression	3-11
3-7. Simple Conceptual Model of Legacy Clutter Filter	3-12
3-8. Minimum Usable Velocity Due to Suppressor Rejection	3-14
3-9. Bias of the Velocity Estimate Due to Clutter or Clutter Residue Signal	3-15
3-10. Bias of Reflectivity Estimate Due to Suppressor Rejection as Related to Spectrum Width	3-16
3-11. Beam Propagation Path Due to Refraction	3-18
3-12. Range-Radar Beam Altitude Nomogram	3-20
3-13. Range Error	3-21
3-14. Meteorological Conditions Likely to Result in Anomalous Propagation	3-23
3-15. WSR-88D Signal Attenuation by the ICAO Standard Atmosphere	3-26
3-16. Attenuation of a 10 cm Signal by Rainfall	3-27
3-17. Deviation in Apparent Range Dependency of Z_e Due to Lack of Radar Beam Filling	3-29
3-18. Typical Antenna Pattern for the WSR-88D and Worst Case Sidelobe Envelope	3-30
3-19. Reflectivity Difference and Angle Subtended Necessary for Signal Contamination through Sidelobe Coupling	3-32
4-1. Functional Configuration of the WSR-88D Unit	4-2
4-2. Block Diagram of the RDA	4-3
4-3. Range Unfolding/Obscuration Pictorial	4-7
4-4. Velocity Dealiasing Pictorial	4-8
5-1. Plots of Z-R Relationships Illustrate the Variability of Various Forms of Precipitation	5-8
5-2. Mean Absolute Percent Difference Between Rainfall Estimates Based on Z-R Relationships	5-9
5-3. Mean Absolute Percent Difference Between Rainfall Estimates Based on Sampling	5-11

Figure	Page
6-1. Environmental Wind	6-2
6-2. Variety of Doppler Velocity Displays	6-4
6-3. Frontal Discontinuity	6-7
6-4. Wind Measurements Using the VAD Technique	6-8
6-5. Horizontal Axisymmetric Flow Fields	6-10
6-6. Combined Rankine Velocity Profile	6-11
6-7. Axisymmetric Mesocyclone Signature	6-13
6-8. Axisymmetric Divergence Signature	6-14
6-9. Distortion of Doppler Velocity Patterns Due to Proximity of Storm to Radar	6-15
6-10. Combinations of Axisymmetric Rotation and Convergence/Divergence	6-17
6-11. Tornadoic Vortex Signature within Mesocyclone Signature	6-18
7-1. Precipitation Band Along a Cold Front Within an ETC	7-3
7-2. Bright Band	7-4
7-3. Schematic of Mesoscale Convective Weather Systems Classification	7-6
7-4. Conceptual Model of a Squall-Line System	7-8
7-5. A Schematic of Mesoscale Convective System Archetypes	7-9
7-6. Line Echo Wave Pattern	7-13
7-7. Conceptual Bow Echo Evolution	7-15
7-8. Conceptual Bow Echo Model	7-16
7-9. Reflectivity Image of a Bow Echo	7-18
7-10. Schematic Diagram of a Distinctive Bow Echo	7-20
7-11. Base Reflectivity Product with a Cold Front	7-21
7-12. VAD Wind Profile	7-23
8-1. Ordinary Cell	8-2
8-2a. Doppler Radar Display of a Supercell at a Low Elevation	8-4
8-2b. Schematic Plan View of an Isolated Classic Supercell Storm near the Surface	8-5
8-2c. Vertical View of Typical Classic (Supercell) Tornado-Producing Cumulonimbus	8-6
8-3. Browning's Classification of Thunderstorm Types	8-8
8-4a. Display of a Multicell Storm (4-panel)	8-9
8-4b. Display of a Multicell Storm (Vertical Cross Section)	8-10
8-5. Display of a Squall Line at Low Elevation Angle	8-11
8-6. Surface to 6 km Wind Difference Versus CAPE	8-13
8-7. Conceptual Storm Motion Diagram	8-16
8-8. Schematic Diagrams Illustrating Bounded and Unbounded Weak Echo Regions	8-18
8-9. Schematic Horizontal and Vertical Radar Sections for an Ordinary Multicell Storm	8-20
8-10. Reflectivity Imagery of Supercell Storms	8-22
8-11a. Supercell Storm Illustration - Horizontal and Vertical Sections	8-24
8-11b. Supercell Storm Illustration - Perspective View	8-25
8-11c. Classic Supercell Storm Draft and Flow Illustration - Three-Dimensional Model	8-26
8-12. A Variety of Documented HP Supercell Reflectivity Configurations	8-29
8-13. Radar Chronology of an LP Storm	8-30
8-14. Top View of an LP Supercell	8-31

Figure		Page
A-1.	Schematic for Radar Detection of a Distributed Target	A-2
A-2.	Radar Cross Section of a Metallic Sphere	A-4
A-3.	Reflectivity Detection Capability of the WSR-88D	A-7
A-4.	Unambiguous Range-Velocity Relationship for the WSR-88D	A-10
A-5.	Theoretical Spectrum Width Versus Range for the WSR-88D	A-14
A-6.	Standard Deviation of the Mean Velocity Estimate	A-19
A-7.	Standard Deviation of the Spectrum Width Estimate	A-21
B-1.	Typical Point Target Detection Capability of the WSR-88D	B-2

LIST OF TABLES

<u>Table</u>	<u>Page</u>
2-1. WSR-88D Radar Characteristics	2-3
3-1. Temporal and Spatial Sampling	3-4
3-2. Height Based on Exponential Minus Height Based on $4/3$ Earth Curvature	3-19
4-1. Representative Fast Scan Sequence	4-10
4-2. Base Data Characteristics	4-11
7-1. Average Echo Intensity Change (dB) Due to Physical Factors Above and Below the Bright Band	7-2

LIST OF SYMBOLS

a	Radius
A	Signal Amplitude
A _e	Effective Aperture Area of the Antenna
b	Gain Constant
c	Speed of Light = $3 \times 10^8 \text{ m s}^{-1}$
dB	Decibel
D	Drop Size
D _e	Diameter of an Equivalent Volume Spherical Raindrop
f	Frequency
f _d	Doppler Frequency
f _n	Nyquist Frequency
f _s	Sampling Frequency
G	Gain
h	Height
h _s	Surface Height
I	Inphase Component of the Complex Signal
k	Multiplicative Factor Determined by Refraction Index Profile
k · a	Equivalent Earth's Radius
K	Complex Index of Refraction
K _p	Two-Way Attenuation
L	Loss Factor
M	Modified Index of Refraction; Mass Liquid Water Content
n	Index of Refraction
N	Refractivity = $(n - 1) \times 10^6$
N ₀	Number Density (Number of Particles Per Unit Volume)
P	Pressure
P _i	Incident Power Density
P _r	Echo (Return) Power
P _t	Peak Transmitted Power
Q	Quadrature Phase Component of the Complex Signal

r	Range to Target
r_a	Unambiguous Range
r_c	Core Radius
R	Rainfall Rate
S	Signal Power
t	Time
T	Air Temperature, ° Kelvin
U	Gating Function
v	Velocity
v_a	Unambiguous Velocity
v_d	Doppler Velocity
v_h	Average Horizontal Wind Velocity Around the Scanning Circle at Height h
v_m	Measured Velocity
v_r	Radial Component of Velocity
v_t	Terminal Fall Velocity for Precipitation Particles
v_T	True Velocity
v_x	Maximum Velocity
V	Voltage
W	Spectrum Width
Z	Reflectivity
Z_e	Equivalent (Effective) Radar Reflectivity Factor
α	Antenna Rotation Rate
β	Azimuth Angle Measured from the Upwind Direction
$\Delta\theta$	Angular Sampling Interval
$\Delta\phi$	Angular Increment
ε	Partial Pressure of Water Vapor, Millibars; Dielectric Constant
η	Target Backscattering Cross Section Per Unit Volume
θ	Angular Distance from Beam Axis
θ_e	Equivalent Angular Distance from Beam Axis
θ_m	Measured Angular Distance from Beam Axis
θ_T	True Angular Distance from Beam Axis

θ_2	Two-way Antenna 3dB Beam Width
θ_{3dB}	Antenna Horizontal Half-Power Beam Width
λ	Radar Wavelength
ρ	Vapor Pressure
σ_b	Target Backscattering Cross Section
σ_d^2	Variance Due to Drop Size Distribution
σ_{do}	Standard Deviation of Drop Terminal Velocities
σ_f	Frequency Standard Deviation
σ_r^2	Variance Due to Antenna Motion
σ_s^2	Variance Due to Wind Shear
σ_t	Time Standard Deviation
σ_t^2	Variance Due to Turbulence
σ_v	Standard Deviation of the Velocity Spectrum
τ	Pulse Width (Duration)
ϕ	Vertical Distance from Beam Axis
ϕ_e	Elevation Angle
ϕ_{3dB}	Antenna Vertical Half-Power Beam Signal
ψ	Initial Phase of Transmitter Signal
ω	Angular Velocity